


198.00 EUR
incl. 19% VAT, plus [shipping](#)



Support:  [Specifications \[EN\]](#)

- Intel® HM67 Express Chipset
- Supports Intel Core™ i3, i5, i7 Mobile Processors
- 2 * SO-DIMM Dual Channel DDR3-1333/1066 up to 16GB
- Intel 82577LM Gigabit LAN
- PCI Express x16 2.0 Slot, PCI Express Mini Card Slot
- Integrated 24-bit Dual Channel LVDS
- 2-ports SATA 6Gb/s & 3-ports SATA 3Gb/s with RAID 0, 1, 5, 10 & JBOD Support
- HDMI, DVI-D, and VGA Video Outputs
- Built-in Watchdog Timer Technology
- Mini-ITX Form Factor (170mm x 170mm)
- Includes CPU Heatsink/Fan for <35W Processors

CPU

Intel Core i3, i5, i7 mobile processors
Socket G2 (rPGA988B), Includes CPU Heatsink / fan for <35W processors

Chipset / Video

Intel HM67 Express Chipset
Intel HD Graphics (requires compatible CPU with built-in GPU)

Memory

2 * SODIMMs Sockets for un-buffered dual channel
DDR3-1333/1066 up to 16 GB

| | |
|----------------------------|---|
| Expansion Slots | 1 * PCI Express x16 2.0 (by 16-lane) slot 1 * PCI Express Mini Card slot |
| Storage | 2 * Serial ATA III 6Gb/s & 3 * Serial ATA II 3Gb/s connectors Support RAID 0,1,5,10 |
| Audio | VIA VT 1705 6-Channel HD Audio |
| Ethernet LAN | Intel 82577LM Gigabit Ethernet LAN |
| LVDS | Onboard 24-bit dual channel LVDS connector |
| USB | Embedded 2 * USB 3.0 & 8 * USB 2.0/1.1 |
| Special Features | Supports ACPI S3, CPU Smart FAN, All solid capacitors Watchdog hardware monitor |
| Rear Panel I / O | 2 * USB 3.0 & 4 * USB 2.0/1.1 ports 1 * PS/2 KB/mouse combo connector 1 * RJ-45 port 1 * HDMI port & 1 * VGA port & 1 * DVI-D port 1 * Audio port (Line-in, MIC and Line-out) 1 * Coaxial Out & 1 * Optical Out |
| Internal I / O | 2 * USB 2.0/1.1 headers for 4 USB ports 1 * 24-bit dual channel LVDS header 1 * Serial header (RS232/422/485) 1 * GPIO header 1 * Audio header, 1 * Front panel header 1 * 24-pin ATX power connector, 1 * 4-pin 12V ATX power connector |
| BIOS | AMI EFI 32MB SMT Flash ROM |
| Certificate | CE, FCC, RoHS, EuP |
| Functional | ATM, Automation, medical Equipment, Security, Digital Signage, POS, General Application, Gaming Machine, Transportation |
| Temperature | Operating within 0~60 centigrade Storage within -20-85 centigrade |
| Form Factor | Mini-ITX Form Factor (170mm x 170mm) |
| Product Accessories | |
| - COM cable | |
| - Manual | |
| - CD | |
| - 1x SATA cable | |
| - I/O shield | |
| - CPU fan | |
| - Thermal grease | |