




74.95 EUR
incl. 19% VAT, plus [shipping](#)



- Applied 100% Solid capacitor design to maximize component reliability
- ECS Durathon Technology ensure the stability, reliability and performance of system.
- ESD Protection prevents computers from electrostatic discharge damage to enhance its durability and lifespan
- ECS MIB III - A friendly interface for overclocking
- Supports DirectX® 12 to enhance graphical performance
- Supports Intel® HD Graphics
- Supports HDMI 1.4a Technology (resolution up to 1920X1200) and HDCP function

Supports Intel® CNVi

CPU	Onboard Intel® Apollo
	Lake processors
	100% Solid capacitor design
GRAPHICS	Supports DirectX® 12
	Supports HDMI 1.4b &
	Premium Audio

MEMORY	Single-channel DDR4
	Memory architecture
	Supports DDR3L 1600
	non-ECC, Un-buffered SO
EXPANSION SLOT	DIMM Memory
	1 X DDR3 SO-DIMM
	socket
	Support up to 8 GB
Storage	1 X M.2 slot for 2242/2260/2280 SSD
	2 X Serial ATAIII 6Gb/s
	6-Channel HD audio
	CODEC Realtek ALC662
Audio	Realtek ALC662 6-channel
	High Definition audio
	CODEC
	Meets performance
	requirements for Microsoft
	WLP 3.08 Vista premium
	and mobile PCs
	Six channel DAC supports
	16/20/24-bit PCM format
	for 5.1 channel audio
LAN	solution
	Emulation of 26 sound
	environments to enhance
	gaming experience
USB	Voice Cancellation and
	Key Shifting in Karaoke
	mode
	Compatible with Direct
REAR PANEL I/O	Sound 3D™, A3D™,
	I3DL2
	Realtek 8111H Gigabit
	Fast Ethernet Controller
	4 X USB3.1 Gen1 port(s) up to 5Gb/s (either rear I/O or front header)
	6 X USB2.0 port(s) Up to 480 Mb/s [Back Panel 2 port(s), Onboard 4 port(s)]
	1 X PS/2 Keyboard & PS/2
	mouse connectors
	1 X Audio port (Line
	Out/Line In/Mic In)
REAR PANEL I/O	1 X RJ-45 port
	1 X HDMI port(s)
	1 X D-Sub (VGA) port(s)
	1 X Display port(optional
	instead of D-SUB (VGA))
	2 X USB3.1 Gen1 port(s)
REAR PANEL I/O	2 X USB2.0 port(s)

**CONNECTORS &
HEADERS**

1 X 24-pin ATX Power
Supply connector
1 X SATA Power
Connector
1 X 4-pin SYS_FAN
connector
1 X Front Panel
switch/LED header
1 X Front panel audio
header
1 X Speaker header
1 X USB 3.1 Gen1 header
(Support additional 2 USB
ports)
2 X USB 2.0 header
(Support additional 4 USB
ports)
1 X CLR_CMOS header
2 X Serial port header
(COM)
1 X Parallel port header
(LPT)
1 X ME_UNLOCK header
1 X Chassis intrusion
header

SYSTEM BIOS

AMI BIOS with 128 MB
SPI Flash ROM
Supports M.I.B III Utility
F7 hot key for boot up
devices option
Dual Display
Support GUI UEFI BIOS
Multi-Language BIOS
Mini ITX Form Factor

FORM FACTOR

170*170

OS Support

Windows 10 64-bit
CE/FCC Certification

Certifications

ErP/EuP Certification
WHQL Certification