

339.00 EUR

incl. 19% VAT, plus [shipping](#)

- For Celeron M 1.5Ghz
- FANLESS carpc system
- 12VDC based !
- Closed front !



CARTFT.COM



Support:  [Assembling Tutorial \[DE\]](#) |  [Assembling Tutorial \[EN\]](#)

Fanless CarPC-barebone for use with Intel P4/Celeron M CPU.

Celeron-M 1.7Ghz is recommended for fanless operation.

| CALU specifications   |                                                                                      |
|-----------------------|--------------------------------------------------------------------------------------|
| Processor (supported) | Intel Pentium M processor or Celeron M processor (Dothan or Banias) 1.3GHz or higher |
| Memory                | Supports DDR 333/266 DIMM RAM                                                        |
|                       | 0.8" low profile                                                                     |
|                       | 2x memory slots !                                                                    |
|                       | Maximum : 2 GB                                                                       |
| Video                 | Intel Extreme Graphics 2                                                             |
|                       | Supports up to 64MB DVMT video memory                                                |
| Audio                 | Software AC '97 Audio CODEC                                                          |

|                              |                                                                                                                                                                                            |
|------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Peripheral Connection</b> | Front :                                                                                                                                                                                    |
|                              | 1 x IEEE 1394 Firewire port<br>1 x USB 2.0 / 1.1 Port<br>1 x MIC Port<br>1 x Ear Phone output Jack<br>Power-on button<br>Reset button<br>Power-on and HDD LED                              |
|                              | Rear :                                                                                                                                                                                     |
|                              | 1 x RS232 COM port<br>1 x parallel printer port<br>1 x RJ45 10/100Mb Fast Ethernet<br>1 x Line-Out output Jack<br>2 x USB 2.0 / 1.1 Ports<br>1 x 15 pin VGA<br>1 x 12v DC Power Jack input |
| <b>Storage</b>               | One 2.5 inch Hard Disk and 9.5mm high.<br>(Support Ultra DMA 33/66/100).                                                                                                                   |
| <b>Weight &amp; Size</b>     | System approximately 3kg (fully equipped).<br>System Dimension: 155 x 255 x 55 mm                                                                                                          |
| <b>Power req.</b>            | 12V, 5A                                                                                                                                                                                    |
| <b>Accessory</b>             |                                                                                                                                                                                            |
| <b>Storage</b>               | Supports all 2.5" standard IDE hard drive, ATA-100/66/33.                                                                                                                                  |
| <b>Scope of supply</b>       | 110V/230V EU power supply<br>Barebone<br>CPU Kühlkörper                                                                                                                                    |

Graphics driver for 800x480 resolution : [Here](#)